





Issued

2012-03-01

Replaces

Page

1 of 3

# Ductile iron wide tolerance couplings

#### STATEMENT BY KIWA

With this product certificate, issued in accordance with the Kiwa Regulations for Product Certification, Kiwa declares that legitimate confidence exists that the products supplied by

### **AVK International A/S**

complying with the technical specifications as laid down in this product certificate and marked with the Kiwa®-mark in the manner as indicated in this product certificate, on delivery, may be relied upon to comply with Kiwa evaluation guideline

**BRL-K775/03** "Ductile iron wide tolerance couplings for different materials: ductile iron, grey iron, steel, PVC-U, PE, fibre cement".

As well as to

**EN 14525:** "Ductile iron wide tolerance couplings for different materials: ductile iron, grey iron, steel, PVC-U, PE, fibre cement, d.d. 01-11-2004"

3. Melhone

Bouke Meekma

Kiwa

Publication of the certificate is allowed.

Advice: consult www.kiwa.nl in order to ensure that this certificate is still valid.

Kiwa Nederland B.V Sir W. Churchill-laan 273 Postbus 70 2280 AB RIJSWIJK The Netherlands

Tel. +31 70 414 44 00 Fax +31 70 414 44 20 E-mail info@kiwa.nl www.kiwa.nl

PRODUCTS RVA C 00 Supplier

AVK International A/S Bizonvej, Skovby 1 GALTEN 8464 Denmark Tel. +45 86 946999 Fax +45 86 944315

e-mail: salg@avk.dk www.avkvalves.com

Certificationprocess consists of initial and regular inspection of:

- qualitysystem
- product



### Ductile iron wide tolerance couplings

#### Productspecification

The products mentioned below belong to this certificate

Supa Maxi™ Types

- 631/00
- 632/00
- 633/00
- 634/00
- 635/00 PN 10 and PN 16

### To be applied to pipes as follows

#### Ductile iron, Grey iron, Steel and Fibre cement

- DN 50, PN 16
- DN 65, PN 16
- DN 80, PN 16
- DN 100, PN 16
- DN 125, PN 16
- DN 150, PN 16
- DN 200, PN 16
- DN 225, PN 16
- DN 250, PN 16
- DN 300, PN 16

#### PVC and PE

- DN 50, PN 6 and PN 16
- DN 65, PN 6 and PN 16
- DN 80, PN 6 and PN 16
- DN 100, PN 6 and PN 16
- DN 125, PN 6 and PN 16
- DN 150, PN 6 and PN 16
- DN 200, PN 6 and PN 16
- DN 225, PN 6 and PN 16
- DN 250, PN 6 and PN 16
- DN 300, PN 6 and PN 16



## Ductile iron wide tolerance couplings

#### Application and use

The products referred to in this evaluation guideline are intended for use in pipe systems for drinking water transport or wastewater transport.

#### Marking

The Kiwa -mark products are marked with the wordmark "KIWA".

Place of the mark: on the outside of the coupling

#### Compulsory specifications:

- · Manufacturer's name or mark;
- Identification of the year of manufacture;
- · Identification of ductile iron;
- · DN and PN rating of flanges when applicable;
- · Reference tot this standard:
- · An identification of the minimum maximum outside diameters (range of external diameters over which the products works);
- PFA of the coupling of the flange adaptor.

#### Method of marking:

- · Non-erasable;
- · visible after assembly.

#### RECOMMENDATIONS FOR CUSTOMERS

Check at the time of delivery whether:

- the supplier has delivered in accordance with the agreement;
- · the mark and the marking method are correct;
- the products show no visible defects as a result of transport etc.

If you should reject a product on the basis of the above, please contact:

- AVK International
- and, if necessary,
- Kiwa Nederland B.V.

Consult the supplier's processing guidelines for the proper storage and transport methods.